

Application No.: 09/408,429

Atty. Docket No.: EMC2-032PUS
(formerly 07072/086001)

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (currently amended) A microprocessor interface disposed between a main memory and a microprocessor, such interface comprising:

a semiconductor integrated circuit having formed therein:

(i) a data rebuffering section having a main memory bi-directional data port, a microprocessor bi-directional data port coupled to the microprocessor, and a plurality of additional bi-directional data ports, such data rebuffering section being adapted to selectively couple data from any one of the plurality of additional bi-directional data ports to the microprocessor bi-directional data port selectively in accordance with a control signal; and

(ii) a main memory interface having a main memory interface bi-directional data port coupled to the main memory and an additional main memory interface bi-directional data port connected to the main memory bi-directional data port of the data rebuffering section, such main memory interface providing control signals to the main memory and for enabling data transfer between the main memory and the microprocessor through the data rebuffering section as data in such data transfer passes between the additional bi-directional data port of the main memory interface and the microprocessor bi-directional data port.

2. (original) The microprocessor interface recited in claim 1 wherein the main memory is a selected one of a plurality of memory types each type having a different data transfer protocol and wherein the main memory interface is configured in accordance with the selected one of the plurality of memory types to provide a proper memory protocol to data

Application No.: 09/408,429

Atty. Docket No.: EMC2-032PUS
(formerly 07072/086001)

being transferred between the microprocessor and the main memory through the main memory interface.

3. (original) The microprocessor interface recited in claim 2 wherein one main memory type is an SDRAM.

4. (original) The microprocessor interface recited in claim 2 wherein one main memory type is a RDRAM.

5. (original) The microprocessor interface recited in claim 1 including a second integrated circuit adapted for controlling the first- mention integrated circuit, such second integrated circuit having thereon a controller adapted for coupling to the main memory interface, such controller being adapted to produce a main memory access control signal, and wherein:

the main memory has a two portions of addressable locations, one portion being addressed by the main memory interface in response to a preselected range of memory location addresses provided by the microprocessor and the other portion being addressed by the main memory interface in response to the memory access control signal provided by the controller.

6. (currently amended) The microprocessor interface recited in claim 1 wherein the data rebuffering section includes:

a selector responsive to the control signal for coupling data between a selected one of the ~~said additional~~ bi-directional data ports and the bi-directional data port of the microprocessor.

7. (currently amended) The microprocessor interface recited in claim 1 wherein the data rebuffering section includes:

a selector responsive to the control signal for coupling the bi-directional

Application No.: 09/408,429

Atty. Docket No.: EMC2-032PUS
(formerly 07072/086001)

data port of the microprocessor to either: a selected one of the ~~the~~ said additional bi-directional data ports; or, the main memory, selectively in accordance with the control signal.

8. (previously presented) The microprocessor interface recited in claim 6 wherein the data rebuffing section includes a data distribution unit having a plurality of ports each one of the ports being coupled to a corresponding one of:

- (i) the selector;
- (ii) a random access memory;
- (iii) an interrupt request controller;
- (iv) the microprocessor; and
- (v) the main memory interface.

9. (original) The microprocessor interface recited in claim 8 wherein the main memory is a selected one of a plurality of memory types each type having a different data transfer protocol and wherein the main memory interface is configured in accordance with the selected one of the plurality of memory types to provide a proper memory protocol to data being transferred between the microprocessor and the main memory through the main memory interface.

10. (original) The microprocessor interface recited in claim 9 wherein one main memory type is an SDRAM.

11. (original) The microprocessor interface recited in claim 9 wherein one main memory type is a RDRAM.

12. (original) The microprocessor interface recited in claim 9 wherein the main memory interface comprises:

a microprocessor/main memory interface control section adapted to provide control signals between such section and the microprocessor and between such section and

Application No.: 09/408,429

Atty. Docket No.: EMC2-032PUS
(formerly 07072/086001)

the controller; and

a main memory controller, such controller being configured in accordance with the selected one of the plurality of memory types to provide the proper memory protocol to data being transferred between the microprocessor and the main memory through the main memory interface.

13. (original) The microprocessor interface recited in claim 9 wherein the main memory interface comprises:

a microprocessor/main memory interface control section adapted to provide control signals between such section and the microprocessor and between such section and the controller; and

a main memory controller, such controller being configured in accordance with a control signal provided thereto by the microprocessor to address a selected one of the plurality of potential memory capacities, the control signal supplied by the microprocessor indicating to the main memory controller the particular one of the plurality of potential memory capacities of the main memory.

14. (original) The microprocessor interface recited in claim 13 wherein the main memory interface comprises:

a microprocessor/main memory interface control section adapted to provide control signals between such section and the microprocessor and between such section and the controller; and

a main memory controller, such controller being configured in accordance with the selected one of the plurality of memory types to provide a proper memory protocol to data being transferred between the microprocessor and the main memory through the main memory interface.

15. (original) The microprocessor interface recited in claim 14 wherein one main memory type is an SDRAM.

Application No.: 09/408,429

Atty. Docket No.: EMC2-032PUS
(formerly 07072/086001)

16. (original) The microprocessor interface recited in claim 14 wherein one main memory type is a RDRAM.

17. (original) The microprocessor interface recited in claim 14 wherein the main memory interface includes an error correction and detection unit coupled between the distributor and the main memory controller.

18 (cancelled)

19. (original) The microprocessor interface recited in claim 5 including a mask to transform the address to an address in the second section of the memory.